

Industry-Leading Monitoring, *Simplified*



The **S-Series** delivers the essential monitoring capabilities you need in a simple, expandable wireless solution. Protect critical assets with wire-free sensors, quick deployment, and reliable performance backed by Sonicu.

Temperature and Humidity Sensor

Ideal for environments where wired sensors aren't practical. Can be programmed to monitor air temperature, humidity, heat index, or warm environments.




Monitoring Range

Temperature
-30°C to 60°C
Humidity
0-100% RH
Warm Environment
-30°C to 80°C

SKUs: S-T, S-HT, S-WE

CO², Temperature, and Humidity with Display

3-in-1 meter with built-in sensors for ambient conditions. Displays room conditions, Battery Percentage, and Last Update. Red/Yellow/Green light provides an eye-catching visual indicator when conditions deviate in real-time.



SKU: S-M06

Monitoring Range

Temperature
-30°C to 60°C
Humidity
0-100% RH
CO²
400 to 5000 ppm

Door Contact Closure Sensor

Delivers additional context to condition changes, delivering peace of mind that excursions are prevented.



SKU: S-M02

Detection Distance

10-15 mm

Occupancy Monitoring Sensor

Ideal for driving energy efficiency measures, cost savings, safety, and security. Bi-directional line-crossing people counting and people flow analysis. Optional blur mode and privacy mask.



SKU: S-M01

Detection Rate

Region Counting: Up to 95%
Line Crossing Counting: Up to 98%
People Flow Analysis: Up to 98%



SoniLink Hub required

For more information and technical specifications for a particular sensor, ask your Sonicu Account Manager or Customer Success Manager for a data sheet.

Food Temperature Monitoring Solution

Ideal for monitoring unprepared food stored in a cooler or freezer or cooked food stored in a warm holding area.



Monitoring Range

Temperature
-40 °C ~ 125 °C

Meter SKU: S-M12
Sensor SKU: SA-AF10

High Temperature Monitoring Solution

Ideal for industrial ovens, sterilizers, and other high-temperature equipment where standard sensors cannot safely operate.



Monitoring Range

Temperature
-50 °C ~ 500 °C

Meter SKU: S-M12
Sensor SKU: SA-A05

Wireless Leak Detector

Ideal for focused, single area leakage monitoring within data centers, server rooms, utility closets, etc.



SKU: S-M03

Trigger Condition

Once liquid level
reaches 0.5mm

Water Rope Leak Detector

Ideal for pipe leakage monitoring behind appliances, along pipes, inside drainage pans, or across other sprawling, hard to reach places.



SKU: S-M04

Trigger Condition

When liquid level
reaches 5mm



SoniLink Hub required

For more information and technical specifications for a particular sensor, ask your Sonicu Account Manager or Customer Success Manager for a data sheet.